


PVC EXTRUSIONS

BELT TECHNICAL DATA SHEET

Belting Edge has noticed a demand for a product that is ISO (International Standards Organization) rated and guarantees the purchaser that all materials used, can be traced from the end product to the raw blend of PVC or PU. All of which is manufactured in South Africa with an official FDA (Food and Drug administration) approved rating.

Belting Edge have invested in this demand and have develop a full range of standard FDA approved PVC and PU extruded profiles. We carry a large stock holding in multiple colours and can manufacture custom orders within 3-5 working days.





Type K	Туре	FDA Material	Colour			Hardness	Minimum Pulley Ø (mm)				Dimensions (mm)		
			White	Blue	Green	Sh A	Underside	Top cover	Transversal	а	b	С	
c b a	K6	PVC	0		10	70	25	35	30	6	5	4	
	K8	PVC	0		•	70	40	60	50	8	5	5	
	K10	PVC	0	•	•	70	70	80	60	10	6	6	
	K13	PVC	0	•	•	70	80	120	80	13	8	8	
	K17	PVC	0	•	•	70	120	150	100	17	11	10	
	K22	PVC	0	•	•	70	200	240	140	22	14	13	
	K6	PU	0			85	40	50	45	6	4	4	
	K8	PU	0			85	60	80	70	8	5	5	
	K10	PU	0			85	70	90	85	10	6	6	
	K13	PU	0		•	85	110	130	120	13	8	8	
	K17	PU	0	•	•	85	140	160	150	17	11	10	

Туре Т	Туре	FDA	Colour			Hardness	Min. Pulley Ø	Dimensions (mm)		Weight	
\bigcap		Material	White	Blue	Green	Sh A	(mm)	b	h	(g/m)	
.	T20	PVC	0	•	•	70	50	20	20	180	
h	T30	PVC	0			70	60	24	30	350	
	T40	PVC	0			70	80	24	40	430	
	T50	PVC	0		00	70	100	28	50	630	
b	T60	PVC	0		•	70	120	28	60	790	

BELTING EDGE cc 14 Lauda Rd, Killarney Gardens, Western Cape, South Africa

Tel. +27 (0) 21 557 0129 - Fax +27 (0) 21 557 3627 huston@beltingedge.co.za - www.beltingedge.com



https://www.facebook.com/beltingedge/







https://www.youtube.com/user/BeltingEdge



https://twitter.com/BeltingEdge